



MS02 IP

Adjustable LED mini light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	45
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	90g
Inrush Current	N/A
Cut Out Size	N/A
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MS02 IP NW	Silver	1W	4000K	12°	73	73	2160	
MS02 IP WW	Silver	1W	3000K	12°	50	50	2000	
MS02 IP 27		1W	2700K	12°	49	49	1944	
MS02 IP RED	Silver	1W	Red	12°				

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

WB/M 01 / WB/M 02	Single bracket / double bracket	Sold Separately
CR135	PTFE cable	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



360° wall light perfect for various applications

1W

1W at 350mA

IP65

IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Mounting plates available

BEAM ANGLE: 12°

