

Accessories

For accessories specific to product ranges visit the relevant sections.

JB1 (Parallel)

Waterproof junction box



Key features	
Max. voltage	30V DC
Max. current	5A
Max. conductor size	1mm ²
Cable diameter	5 - 6.5mm ²
IP rating	IP68 (2m)
Wiring	Parallel
Inputs	1
Outputs	1 - 3

Use in conjunction with
GL018

JB3

Waterproof junction box



Key features	
Max. voltage	400V AC
Max. current	30A
Max. conductor size	4mm ²
Cable diameter	3 - 12mm ²
IP rating	IP66
Wiring	Parallel
Inputs	1
Outputs	1 - 7

Use in conjunction with
GL016RGBW GL090RGBW

JB5 (Parallel)

Gel filled waterproof junction box



Key features	
Max. voltage	250V AC
Max. current	16A
Max. conductor size	1.5mm ²
Cable diameter	6.5 - 12mm ²
IP rating	IP68 (1.3m)
Wiring	Parallel
Inputs	1
Outputs	1 - 3

Use in conjunction with
BL03 GL018
GL034 GL038
GL200 WL339
WL341

JB7

5 pole screw terminal IP68 connector



Key features (RGBW only)	
Max. voltage	24V
Max. current	1.4A
Max. conductor size	4mm ²
Cable diameter	7 - 10.5mm ²
IP rating	IP68 (1.3m)
Wiring	Parallel
Inputs	1
Outputs	1

Use in conjunction with
GL016RGBW GL090RGBW

JB2 (Series)

Waterproof junction box



Key features	
Max. voltage	48V DC
Max. current	700mA
Max. conductor size	1mm ²
Cable diameter	5 - 6.5mm ²
IP rating	IP68 (2m)
Wiring	Series
Inputs	1
Outputs	1 - 3

Use in conjunction with
BL01 GL016 GL019
GL021 GL022 GL040
UL010 UL030 SL030
SL130 SL040 SL220
GL100

JB4 (Series)

Gel filled waterproof junction box



Key features	
Max. voltage	120V DC
Max. current	700mA
Max. conductor size	1.5mm ²
Cable diameter	3 - 12mm ²
IP rating	IP66
Wiring	Series
Inputs	1
Outputs	1 - 7

Use in conjunction with
BL01 GL016 GL019
GL021 GL022 GL040
UL010 UL030 SL030
SL130 SL040 SL220
GL100

JB6

Inline IP68 gel filled cable connector



Key features	
Max. voltage	250V AC
Max. current	6A
Max. conductor size	0.75mm ²
Cable diameter	4.8 - 6mm ²
IP rating	IP68 (1.3m)
Wiring	Inline
Inputs	1
Outputs	1

Use in conjunction with
WCR 275 BLACK
Ideal for extending cable when it's not long enough

WC 5-9

Quick release waterproof connector



Key features (RGBW only)	
Max. voltage	250 AC / 50 DC
Max. current	10A
Max. conductor size	4mm ²
Cable diameter	5 - 9mm ²
IP rating	IP68 (1.3m)
Wiring	Inline
Inputs	1
Outputs	1

Use in conjunction with
BL03 GL034
GL038 GL200
SL220 WL339
WL340 WL341
WL342

WCR 275 Black

2-core rubber cable



Key features		Use in conjunction with	
Cable	H05RN-F 2 x	JB1	JB2
	0.75mm ²	JB4	JB6
	Outer diameter 6mm		
Material	Copper cable, rubber outer		
Length	100m reel		
Indoor / outdoor	Suitable for permanent outdoor use		

WCR 375 Black

3-core rubber cable



Key features		Use in conjunction with	
Cable	H05RN-F 3 x	JB1	JB5
	0.75mm ²	WC 5-9	
	Outer diameter 6mm		
Material	Copper cable, rubber outer		
Length	100m reel		
Indoor / outdoor	Suitable for permanent outdoor use		

UY2 Connector

Quick waterproof connector



Key features		Use in conjunction with
IP rating	IP65	ML01
Wiring	Series	
Waterproof type	Gel	
Material	Plastic	