

Surface & Suspended



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

Guarantee

7 years (product), 5 years (emerg battery), 2 years (on-site)

Features & benefits

Energy efficient up to 100lm/W

Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)

Suspend as an individual luminaire or (by custom request) connect together to make a continuous run

>10% uplight when surface mounted


Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options

DALI-2 driver is switchable to enable lower lumen outputs

Supplied with suspension kit

DALI Dimmable Fitting with on-off PIR Sense

Beam angle: 80°



Versa Tile Black 1500mm

UGR19 architectural linear suitable for surface, suspension or wall mount

Features

IK rating	IK02
IP rating	IP20
CSP switchable	Single CCT
Sensor option	PIR & Daylight with accessories
Dimmable option	Yes (DALI-2, PUSH-DIM)
Input	220-240V AC
LED lifetime	L80 54,000h
Colour rendering Index	CRI>80
Colour consistency	SDCM6
Emergency option	Yes, Self-Test

Installation information

Install connector type	Push-fit terminal, loop-in/loop-out
Inrush current	Standard: 16A 672µs, DALI: 30A 45µs
Construction material	Aluminium Housing, Polystyrene Diffuser
Weight	4.25kg
Maximum ambient temperature	0°C - 40°C
Electric class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Type	W	CCT	∠°	lm	lm/W	EM	Energy
VTBIN	Standard	45W	4000K	80	4500	100	-	
VTBINEM	Emergency	45W	4000K	80	4500	100	215	
VTBINP	PIR sensor	45W	4000K	80	4500	100	-	
VTBINPEM	Emergency	45W	4000K	80	4500	100	215	
VTBID	DALI-2 dimmable	45W	4000K	80	4500	100	-	
VTBIDEM	Emergency DALI-2 dimmable	45W	4000K	80	4500	100	215	
VTBIDP	DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	4500	100	-	
VTBIDPEM	Emergency DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	4500	100	215	

Energy rating is a reflection of the LED light source.

Wiring information

Cable / flying lead	0.75-2.5mm²
Type of wiring required	Parallel

Accessories

VTBWALL	Black Wall Mount Kit	Sold Separately
VTBCON	Black Connect Joint Kit	Sold Separately

Surface & Suspended



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

Guarantee

7 years (product), 5 years (emerg battery), 2 years (on-site)

Features & benefits

Energy efficient up to 110lm/W

Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)

Suspend as an individual luminaire or (by custom request) connect together to make a continuous run

>10% uplight when surface mounted


Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options

DALI-2 driver is switchable to enable lower lumen outputs

Supplied with suspension kit

DALI Dimmable Fitting with on-off PIR Sense

Beam angle: 80°



Versa Tile Silver 1500mm

UGR19 architectural linear suitable for surface, suspension or wall mount

Features

IK rating	IK02
IP rating	IP20
CSP switchable	Single CCT
Sensor option	PIR & Daylight with accessories
Dimmable option	Yes (DALI-2, PUSH-DIM)
Input	220-240V AC
LED lifetime	L80 54,000h
Colour rendering Index	CRI>80
Colour consistency	SDCM6
Emergency option	Yes, Self-Test

Installation information

Install connector type	Push-fit terminal, loop-in/loop-out
Inrush current	Standard: 16A 672µs, DALI: 30A 45µs
Construction material	Aluminium Housing, Polystyrene Diffuser
Weight	4.25kg
Maximum ambient temperature	0°C - 40°C
Electric class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Type	W	CCT	Beam angle	lm	lm/W	EM	Energy
VTSIN	Standard	45W	4000K	80	5000	110	-	
VTSINEM	Emergency	45W	4000K	80	5000	110	240	
VTSINP	PIR sensor	45W	4000K	80	5000	110	-	
VTSINPEM	Emergency	45W	4000K	80	5000	110	240	
VTSID	DALI-2 dimmable	45W	4000K	80	5000	110	-	
VTSIDEM	Emergency DALI-2 dimmable	45W	4000K	80	5000	110	240	
VTSIDP	DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5000	110	-	
VTSIDPEM	Emergency DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5000	110	240	

Energy rating is a reflection of the LED light source.

Wiring information

Cable / flying lead	0.75-2.5mm ²
Type of wiring required	Parallel

Accessories

VTWALL	Silver Wall Mount Kit	Sold Separately
VTSCON	Silver Connect Joint Kit	Sold Separately



Versa Tile White 1500mm

UGR19 architectural linear suitable for surface, suspension or wall mount

Features

IK rating	IK02
IP rating	IP20
CSP switchable	Single CCT
Sensor option	PIR & Daylight with accessories
Dimmable option	Yes (DALI-2, PUSH-DIM)
Input	220-240V AC
LED lifetime	L80 54,000h
Colour rendering Index	CRI>80
Colour consistency	SDCM6
Emergency option	Yes, Self-Test

Installation information

Install connector type	Push-fit terminal, loop-in/loop-out
Inrush current	Standard: 16A 672µs, DALI: 30A 45µs
Construction material	Aluminium Housing, Polystyrene Diffuser
Weight	4.25kg
Maximum ambient temperature	0°C - 40°C
Electric class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Type	W	CCT	Beam angle	lm	lm/W	EM	Energy
VTWIN	Standard	45W	4000K	80	5500	120	-	A D
VTWINEM	Emergency	45W	4000K	80	5500	120	260	A D
VTWINP	PIR sensor	45W	4000K	80	5500	120	-	A D
VTWINPEM	Emergency	45W	4000K	80	5500	120	260	A D
VTWID	DALI-2 dimmable	45W	4000K	80	5500	120	-	A D
VTWIDEM	Emergency DALI-2 dimmable	45W	4000K	80	5500	120	260	A D
VTWIDP	DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5500	120	-	A D
VTWIDPEM	Emergency DALI-2 Dimmable with On-Off PIR Sensor	45W	4000K	80	5500	120	260	A D

Energy rating is a reflection of the LED light source.

Wiring information

Cable / flying lead	0.75-2.5mm ²
Type of wiring required	Parallel

Accessories

VTWWALL	White Wall Mount Kit	Sold Separately
VTWCON	White Connect Joint Kit	Sold Separately

Surface & Suspended



Slim depth of just 38mm



UGR19 for low glare



75% down / 25% up ratio uses light efficiently

Guarantee

7 years (product), 5 years (emerg battery), 2 years (on-site)

Features & benefits

Energy efficient up to 120lm/W

Choice of White (RAL9003), Black (RAL9005) or Silver (RAL9006)

Suspend as an individual luminaire or (by custom request) connect together to make a continuous run

>10% uplight when surface mounted

Configurable using our unique VERSABOX design to realise a range of lumen output, driver and sensor options

DALI-2 driver is switchable to enable lower lumen outputs

Supplied with suspension kit

DALI Dimmable Fitting with on-off PIR Sense

Beam angle: 80

