HUNZA
PURE OUTDOOR LIGHTING

Arch Wall Square

PureLED

Project _____

Type _____

Source _____


Notes _____

SPECIFICATIONS

LED Chip	Cree CXB 1830 field replaceable LED board
Luminaire Output*	3000 lumens @ 700mA (26W)
Lumens Per Watt*	115 lumens @ 26W minimum
LED Life Expectancy	50,000 hours L70
CRI (3000K)	90+
Ingress Protection	IP66
Warranty	Electronics = 5 years (Excludes third party lamps and power supplies) Aluminium = 5 years
Standards	CE IEC/BS/AS/NZ 60598

*Delivered from the luminaire with an unobstructed beam





PRODUCT CONFIGURATION

Please fill in appropriate codes into boxes provided

Luminaire

☑ W/ARCSQ

Product Order Code: W/ARCSQ

Power ☐ ---------- **Material/Finish** ☐ ---------- **Beam** ☐ ---------- **Colour** ☐

SR	Constant Current Input, Series Wired, 26W Requires Constant Current 0-10V Dimmable Driver (supplied separately). Fixture Input: 37Vf @700mA maximum.
S	Constant Current Input, Series Wired, 26W Requires Constant Current Driver (not supplied). Fixture Input: 37Vf @700mA maximum.
D24	24VDC Input, Parallel Wired, 26W Requires 24VDC Constant Voltage Power Supply (not supplied). Fixture Input: 24VDC, 26W (700mA).
R	90-264VAC Input, Parallel Wired, 26W Integral Constant Current 0-10V Dimmable Driver (supplied and installed). Fixture Input: 120 - 277VAC (26W, 700mA).

Aluminium Powder Coat Colour Options

EBK	Black
EBZ	Bronze
EOGR	Olive green
EWH	White
EWB	White Birch
EDG	Dark Grey
ESTAR	Silver Star
ECT	Corten
FS	Fine Silver

TYP2	Type 2
TYP4	Type 4
95	95 Degrees

2	2700K
3	3000K
4	4000K

HUNZA
PURE OUTDOOR LIGHTING

Address
130 Felton Mathew Ave
Saint Johns, Auckland 1072
New Zealand

Contact
Ph: +64 9 528 9471
E: info@hunza.co.nz
Web: hunzalighting.com

This document contains proprietary information of Hunza™. Its receipt or possession does not convey any rights to reproduce or disclose its content. Due to continued product improvements, specifications may change without notification.

Installation, IES & Guides are available online

MADE IN NEW ZEALAND

LUMINAIRE INFORMATION

CNC machined from the following materials

Powder Coated Aluminium
Virgin, high corrosion resistant, low copper content (0.001%) aluminium with chromate substrate, and a highly UV-resistant polyester powder coat.

Gaskets
Silicone, iron impregnated 220ºC (428ºF).

Lens
Extra clear optical silicone TIR.


Cable
SWOOJ cable.

Mounting
The wall plate is fixed to the surface using four stainless steel screws.

Luminaire Weight
6kg (13lbs 4oz) head only


BEAM ANGLES


Extra clear optical silicone TIR.







TYPE 2





TYPE 4






95º


WIRING GUIDE

Diagrams are a guide only, wire colours and polarity may change depending on fixture and country.


Circuit: Contant Current - Wired in Series
Please see installation instructions for full details.



Circuit: 120 - 277VAC - Wired in Parallel
Please see installation instructions for full details.



Circuit: 24VDC - Wired in Parallel
Please see installation instructions for full details.



HUNZA
PURE OUTDOOR LIGHTING

Address
130 Felton Mathew Ave
Saint Johns, Auckland 1072
New Zealand

Contact
Ph: +64 9 528 9471
E: info@hunza.co.nz
Web: hunzalighting.com

This document contains proprietary information of Hunza™. Its receipt or possession does not convey any rights to reproduce or disclose its content. Due to continued product improvements, specifications may change without notification.

Installation, IES & Guides are available online

MADE IN NEW ZEALAND