


Spike Spot High Power RGBW PURE LED

SPECIFICATIONS



LED Chip	LED Engin Plug and Play field replaceable LED board
Luminaire Output	1000 total Lumens @250mA (20 Watts) with all colours on, Delivered from luminaire with unobstructed beam
Lumens Per Watt	54 Lumens minimum @ 20 watts, delivered from luminaire with unobstructed beam
CRI (6500K)	75CRI White - 6500K
Colour Temperatures	6500K White + Red, Blue, Green
Beam Angles	15, 30, 40, 70
Ingress Protection	IP66
Warranty	Electronics = 5 years Body Aluminium = 5 years
Standards	AS/NZS 61046 cUL 2108, 1598 CSA C22.2 No. 250.0-08, No. 250.0 CE



PRODUCT CONFIGURATION

Please fill in appropriate codes into boxes provided

Cat. No. SS/HPRGBW

Luminaire	Power	Material/Finish	Beam	Accessories
<input type="text" value="SS/HPRGBW"/>	<input type="text" value="SR"/>	<input type="text"/>	<input type="text"/>	<input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
<input type="text" value="SR"/> 250mA Input, Series Wired 20W		ALUMINIUM <input type="text" value="EBK"/> BLACK <input type="text" value="EBZ"/> BRONZE <input type="text" value="EOGR"/> OLIVE GREEN <input type="text" value="EWH"/> WHITE <input type="text" value="EWB"/> WHITE BIRCH <input type="text" value="EDG"/> DARK GREY <input type="text" value="ESTAR"/> SILVER STAR <input type="text" value="ECT"/> CORTEN	<input type="text" value="15"/> 15° <input type="text" value="30"/> 30° <input type="text" value="40"/> 40° <input type="text" value="70"/> 70°	<input type="text" value="LKN"/> LOCKING KNUCKLE <input type="text" value="SNT"/> SNOOT <input type="text" value="GG"/> GLARE GUARD <input type="text" value="LF"/> FROSTED LENS <input type="text" value="CJK"/> CABLE JOINT KIT
SERIES DRIVER: Constant current driver (included, supplied separate to fixture). Individual channels require: Red 15vdc Green 21.6vdc Blue 19.2vdc White 22.4vdc @250mA maximum.				
<input type="text" value="ADDITIONAL COMMENTS:"/>				

Specifications may change without notification V2 12/22

LUMINAIRE CONSTRUCTION

CNC machined from one of the following metals:

Aluminium:

Body: high corrosion resistant 63.5mm (2^{1/2}" x 10mm (3/8") aluminium.

Driver Housing (Retro™): solid aluminium 63.5mm (2^{1/2}" x 3.25mm (1/8") tube with chromate substrate and high UV resistant polyester "E" powder coat.

Colours:

Black, Bronze, Silver Star, White, White Birch, Olive Green, Dark Grey, Corten.

Knuckles:

Aluminium luminaires: 360° rotation and 0-90° elevation, solid brass with anti rust spring.

Cable:

Water resistant rubber with HUNZA™ Anti-Syphon™ barrier system.

Lens:

10mm (3/8") Extra clear, low iron, shatter resistant glass.

Lifetime warranty

Gaskets:

Silicone, iron impregnated 220°C (428°F)

Mounting:

Series: Ground spike 150mm (6") inserted directly into the earth.

Retro™ (110/240-12volt): driver housing pole 395mm (15^{1/2}") is directly mounted into the earth.

Flange Mount option is available for hard surfaces.

Luminaire Weight:


Low voltage:

Alum: 0.870 (1lb 15oz)


Retro™

Alum: 1.500 (3lb 5oz)

ACCESSORIES



Snoot



Glare Guard




Locking Knuckle


BEAM ANGLES

High efficiency PMMA TIR lenses. Field replaceable


IES files available for download: hunzaligning.com/downloads




15° FWHM
TIR



30° FWHM
TIR



40° FWHM
TIR



70° FWHM
TIR



WIRING GUIDE

Available for download: hunzalighting.com/downloads

CONSTANT CURRENT - SERIES WIRED

Diagrams are a guide only, wire colours and polarity may change depending on fixture and country.

Driver Channels/ Groups	Wire Colour	LED Channels
Output (1+)	Orange Wire +	Red Channel +
Output (1-)	Orange/White Wire -	Red Channel -
Output (2+)	Green Wire +	Green Channel +
Output (2-)	Green/White Wire -	Green Channel -
Output (3+)	Blue Wire +	Blue Channel +
Output (3-)	Blue/White Wire -	Blue Channel -
Output (4+)	Brown Wire -	White Channel +
Output (4-)	Brown/White Wire -	White Channel -



Specifications may change without notification V2 12/22