

Pole Spot ULTRA 35

PROJECT:

TYPE:


SOURCE:

NOTES:

SPECIFICATIONS



LED Chip	Cree CXA 1830 field replaceable LED board
Luminaire Output	2700 Lumens minimum @ 700mA (26 watts), delivered from the Luminaire with unobstructed beam
Lumens Per Watt	100 Lumens minimum @ 26 watts, delivered from Luminaire with unobstructed beam
CRI (3000K)	80 Standard, 90+ Optional
Colour Temperatures	2700K, 3000K, 4000K
Beam Angles	13, 20, 25, 34
Ingress Protection	IP66
Warranty	Electronics = 5 years Body Aluminium = 5 years
Standards	BS/EN 60598.2.2 cUL 1598, CSA C22.2 No. 250.0 CE



PRODUCT CONFIGURATION

Please fill in appropriate codes into boxes provided

Cat. No. PS/U35

Luminaire	Power	Material/Finish	Beam	Colour	Accessories
PS/U35					
PSFM/U35					
SR 700mA Input, Series Wired 26W D24 24VDC Input, Parallel Wired R RETRO, 120-277VAC Input, Parallel Wired SERIES REMOTE: Constant current driver (included) individual fixtures require 37vdc @ 700mA maximum (non dimming). Dimming option available (0-10 volt). 24VDC DRIVER: Input: 24vdc constant voltage. Output: 36vdc @ 700mA constant current (non dimming). Note: not for USA. RETRO 110-277vac DRIVER: Constant current driver (included). Input: 120, 240, 277 volts Output: 30 watts total 37vdc @ 700mA (non dimming). Dimming option available (0-10 volt).	ALUMINIUM EBK BLACK EBZ BRONZE EOGR OLIVE GREEN EWH WHITE EWB WHITE BIRCH EDG DARK GREY ESTAR SILVER STAR ECT CORTEN	13 13° 20 20° 25 25° 34 34°	2 2700K 3 3000K 4 4000K 39 3000K, 90+ CRI	CJK CABLE JOINT KIT ULT35GG GLARE GUARD HCL/U35 HEX CELL LOUVRE MOUNTCAGE MOUNTING CAGE* ULT35SNT SNOOT	

*Only available for Flange Mount Version

ADDITIONAL COMMENTS:

LUMINAIRE CONSTRUCTION

CNC machined from one of the following metals:

Aluminium:

Body: 101mm (4") high corrosion resistant aluminium rod with chromate substrate and high UV resistant polyester powder coat.
Pole: 76mm (3") aluminium tube.
Colours: Black, Bronze, Silver Star, White, White Birch, Olive Green, Dark Grey, Corten.

316 Stainless Steel:

Bracket: laser cut and folded 316 stainless steel.

Adjustability:

The fully adjustable head allows 360 degree rotation and 0-120 degree elevation.

Cable:

Water resistant rubber.

Gaskets:

Silicone, iron impregnated 220°C (428°F).

Step Lens:

12mm (1/2") extra clear, low iron, shatter resistant glass.
Lifetime warranty.


Mounting:

The pole is cast into concrete or mounted via flange mount - please refer to the Hunza website for mounting instructions.


Luminaire Weight:

4kg (9lb)

ACCESSORIES




Glare Guard



Hex Cell Louvre



Mounting Cage




Snout


BEAM ANGLES

High efficiency Reflectors. Field replaceable


IES files available for download: <http://www.hunzalighting.com/download.php>




13° FWHM REFLECTOR



20° FWHM REFLECTOR






25° FWHM REFLECTOR



34° FWHM REFLECTOR

WIRING GUIDE

Available for download: www.hunzalighting.com/download.php



Diagrams are a guide only, wire colours and polarity may change depending on fixture and country

Specifications may change without notification

Aug 2017