

MLCMBP002ANTBRS


Antique Brass





MATERIAL	BRASS CERAMIC GLASS
HEIGHT	9.5CM 3.74"
WIDTH DIAMETER	27CM 10.63"
LENGTH PROJECTION	n/a
WEIGHT	0.9KG 1.98lbs
LAMPHOLDER	E27 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	II
SHADE	MLCS016 BO-IP.GLASS GLWP01
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	MLOCA001 2 Core Round Brown Braid Rubber

Fixing Bracket MLROSE39







I) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.






Antique Silver MLCMBP002ANTSLV





MATERIAL	BRASS CERAMIC GLASS
HEIGHT	9.5CM 3.74"
WIDTH DIAMETER	27CM 10.63"
LENGTH PROJECTION	n/a
WEIGHT	0.9KG 1.98lbs
LAMPHOLDER	E27 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	II
SHADE	MLCS016 BO-IP.GLASS GLWP01
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	MLOCA002 2 Core Round Black Braid Rubber

Fixing Bracket MLROSE39














MLCMBP002PCMBK Matt Black





MATERIAL	BRASS CERAMIC GLASS
HEIGHT	9.5CM 3.74"
WIDTH DIAMETER	27CM 10.63"
LENGTH PROJECTION	n/a
WEIGHT	0.9KG 1.98lbs
LAMPHOLDER	E27 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	II
SHADE	MLCS016 BO.IP.GLASS GLWP01
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	MLOCA002 2 Core Round Black Braid Rubber

Fixing Bracket MLROSE39







I) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.





MLCMBP002POLBRS


Polished Brass





MATERIAL	BRASS CERAMIC GLASS
HEIGHT	9.5CM 3.74"
WIDTH DIAMETER	27CM 10.63"
LENGTH PROJECTION	n/a
WEIGHT	0.9KG 1.98lbs
LAMPHOLDER	E27 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	II
SHADE	MLCS016 BO-IP.GLASS GLWP01
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	MLOCA002 2 Core Round Black Braid Rubber

Fixing Bracket MLROSE39







Product Notes:

1) Lamps not included with lightfixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.)

Products wired to UL standards will operate at 110/120vwith the appropriate lampholders.






MLCMBP002SATBRS Satin Brass





MATERIAL	BRASS CERAMIC GLASS
HEIGHT	9.5CM 3.74"
WIDTH DIAMETER	27CM 10.63"
LENGTH PROJECTION	n/a
WEIGHT	0.9KG 1.98lbs
LAMPHOLDER	E27 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	II
SHADE	MLCS016 BO-IP.GLASS GLWP01
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	MLOCA002 2 Core Round Black Braid Rubber

Fixing Bracket MLROSE39







Product Notes:

1) Lamps not included with lightfixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.)

Products wired to UL standards will operate at 110/120vwith the appropriate lampholders.

