

						
Product Name	T-3350 Driver	T-M-97757 Driver	T-MP15 Driver	T-M-97404 Driver	T-D-93010236 Driver	T-D-93010235 Driver
Product Code	T-3350	T-M-97757	T-MP15	T-M-97404	T-D-93010236	T-D-93010235
Input v	230	230	230	230	230	230
Output v	3-10v dc	12-48v	44v	2-18v	12-48v	12-43v
Output w	350mA 3w	350mA 18w	60-350mA 15w	700mA 12w	700mA 36w	1050mA 48w
IP Rating	IP67	IP67	IP20	IP67	IP65	IP65
Cable Length	200mm	400mm	None	400mm	IP 500mm / OP 350mm	IP 500mm / OP 350mm
Dimmable	No	1-10v	No	No	0-10v C.Source	0-10v C.Source
Max Distance	20m	20m	60m	20m	60m	60m
Auto Re-set	Yes	Yes	Yes	Yes	Yes	Yes
Mounting	Case or Canister	Case or Canister	Case or Canister	Case or Canister	Case or Canister	Case or Canister
Dimensions	25mm x 34mm x 32mm	34mm x 40mm x 170mm	19mm x 34mm x 115mm	22mm x 24mm x 105mm	30mm x 41mm x 153mm	30mm x 41mm x 153mm
LuxR Modux 1	1-2	2-14	1-12	n/a	n/a	n/a
LuxR Modux 2	n/a	n/a	n/a	1-5	1-12	n/a
LuxR Modux 4	n/a	n/a	n/a	1-3	2-7	n/a
Hunza PureLED	n/a	n/a	n/a	1-3 (a)	1-8 (a)	2-7 (b)

**Notes:**

(a) Border, Euro Spot, Twig, Walkway and, Mouse Lites – 700mA

(b) All other Hunza PureLED products – 1050mA

						
Product Name	T-LPC-35-1050 Driver	T-LD25W Driver	T-2000B Driver			
Product Code	T-LPC-35-1050	T-LD25W	T-2000B			
Input v	230	230	230			
Output v	3-30v	4-12v	18-30v			
Output w	1050mA 33w	2080mA 25w	2000mA 60w			
IP Rating	IP67	IP66	IP30			
Cable Length	600mm	150mm	150mm			
Dimmable	No	Yes - 1-10v	Yes - Phase			
Max Distance	20m	TBC	TBC			
Auto Re-set	Yes	Yes	Yes			
Mounting	Case or Canister	Case or Canister	Case or Canister			
Dimensions	30mm x 40mm x 148mm	80mm x 80mm x 45mm	128mm x 60mm x 32mm			
LuxR Modux 1	n/a	n/a	n/a			
LuxR Modux 2	n/a	n/a	n/a			
LuxR Modux 4	n/a	n/a	n/a			
Hunza PureLED	1-5	High Power 1-2	High Power 2-5			

**Notes:**

- (a) Border, Euro Spot, Twig, Walkway and, Mouse Lites – 700mA
- (b) All other Hunza PureLED products – 1050mA