


# Pagoda Lite PURE LED

Cat. No. PGL/L



**PURE LED**  
Pure Performance

## UK & European Specification

The Pagoda Lite PURELED produces general illumination, suitable for area lighting on porches, patios, decks and entrance ways.

The lens is manufactured from high quality UV stable polycarbonate, with a stainless steel mesh lining to reduce glare. An opal frosted lens is also available as an option.

The Hunza PURELED system uses the latest Cree MTG-2 LED chips for maximum performance and long life. Power supply options include a choice of integral 12 volt driver, an integral Retro™ 110/240 volt driver or an external remote driver. The integral Retro driver has a 0-10 volt dimming function. PURELED incorporates an innovative Plug-and-Play system for easy replacement or upgrade of either the LED engine or integral driver.

The Retro™ version is ideal for installations where mounting an external power source is a problem, e.g. on a brick wall where there is no space to recess the driver. The base size increases in depth to accommodate the encapsulated IP66 dimmable driver.

\*At 700mA this fitting is the equivalent of a 35w halogen fitting.

\*At 1050mA this fitting is the equivalent of a 50w halogen fitting.

## Ordering Information

Luminaire	Driver mA	Colour Temp	Accessories	Material/Finish
PGL/L	S - Series	3 - 3000K	LENSBOLOP - Opal Lens	BK - Black
	D7 - 12v 700mA	4 - 4000K	WBAP - Wall Box Adapt	BZ - Bronze
	RE - 240v Retro			GN - Green
	RU - 110v Retro			STAR - Silver Star
				WH - White
				WB - Birch
				DG - Dark Grey
				OG - Olive Green
				RG - Beige
				PR - Primrose

Example: **PGL/L S 3 LENSBOLOP BK**

Luminaire Construction	Features	Technical Information
<p><b>CNC machined from the following metal:</b></p> <p><b>Aluminium:</b> Body: High corrosion resistant 63.5mm (2.5") x 10mm (25/64") aluminium.</p> <p><b>Base &amp; Mounting Plate:</b> Cast from virgin high corrosion resistant CC401 low copper aluminium alloy with chromate substrate and high UV resistant polyester powder coat – Black, Bronze, Green, Silver Star, White, Birch, Dark Grey, Olive Green, Beige, Primrose.</p> <p><b>Copper:</b> <b>Body:</b> 63.5mm (2.5") x 10mm (25/64"). <b>Base:</b> Hand Spun Copper 2mm (5/64") <b>Mounting Plate:</b> Forged Brass (Retro™)</p> <p><b>Stainless Steel:</b> <b>Body:</b> 63.5mm (2.5") x 9mm (11/32") rod <b>Base:</b> Investment cast and CNC machined <b>Mounting Plate:</b> Investment cast and CNC machined (Retro™)</p> <p><b>Luminaire Weight</b> <i>12 volt</i> Alum: 0.510kg (1lb 1oz)           Cop: 1.220kg (2lb 11oz)           SS: 1.120kg (2lb 7oz) <i>Retro™</i> Alum: 0.840kg (1lb 13oz)           Cop: 1.500kg (3lb 4oz)           SS: 1.460kg (3lb 3oz)</p>	<p><b>Lens:</b> UV stable clear polycarbonate with stainless anti-glare mesh.</p> <p><b>Gasket:</b> Silicone, iron impregnated 220°C (428°F)</p> <p><b>Accessories:</b> Opal Lens (Cat.LENSBOLOP) Wall Box Adaptor (Cat. WB)</p> <p><b>Mounting:</b> 12 Volt: The luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth.</p> <p>Retro™ luminaire (110/240-12volt): a mounting plate is fixed to the wall using two screws and the luminaire is fitted to the mounting plate.</p>	<p><b>Standards</b> AS/NZS61046 IP66 UL1838</p> <p><b>LED</b> Cree MTG-2 Plug and Play, field replaceable LED board.</p> <p><b>Lumen Output:</b> 510 lm at 1050mA <b>Lumens Per watt:</b> 85 at 6watts <b>CRI Warm White (3000k):</b> 85+ <b>Colour Temp:</b> 3,000 or 4,000K</p> <p style="text-align: center;"><b>Power Supply</b></p> <p><b>Series (External) Driver</b> Constant current driver Output: 6vdc at 1050mA maximum</p> <p><b>Integral 12 Volt Driver</b> Hunza™ Plug and Play Driver Input: 12vac, 7 watt total Output: 6vdc nominal, 350 / 700 / 1050mA</p> <p><b>Transformer</b> Hunza™ Wall Mount Transformer for use with integral 12 volt driver</p> <p><b>Retro 110/240 Volt Driver</b> Hunza™ Retro Driver Input: 120/240vac, 5 watt total Output: 6vdc, 700mA 0-10 volt dimming</p>